

ALKA 200

HIGH FOAMING ALKALI CLEANER

ALKA 200 is a self-foaming alkali cleaner and degreaser for cleaning floors, walls and processing equipment in general food processing areas. **ALKA 200** is formulated with a blend of alkali builders, chelating agents, detergents and solvents, it is effective for removing fatty and greasy soils from all hard surfaces. **ALKA 200** may be used with foam generating equipment, pressure washing, or manual cleaning. Safe on aluminum surfaces.



FOR USE BY:

Airports
Apartment Buildings
Buildings Maint.
Grounds Maint.
Bus Lines
Corrections
Daycares
Hospitals
Hotels/Motels
Hospitals
Military
Nursing Homes
Packaging Plants
Parks and Rec.
Processing Plants
Restaurants
Sanitation Dept.
Schools
Street Dept.
WWTP

FOR USE ON:

Floors
Walls
Food Processing Areas
Aluminum Surfaces

FEATURE-BENEFIT:

Liquid Alkali Cleaner
High Foaming
Excellent for regular clean-up of floors, walls, and equipment in meat rooms and food plants.

ALKA 200 HIGH FOAMING ALKALI CLEANER

DIRECTIONS:

FOR CLEANING FLOORS AND WALLS: Dilute 2-4 oz. per gallon
FOR PROCESSING EQUIPMENT: Dilute 4-8 oz. per gallons

Allow solution to remain on surfaces for at least 15 minutes.
Rinse thoroughly with potable water.

TECHNICAL DATA:

Appearance: Clear colorless
Odor: Odorless
Specific Gravity: 1.11
pH: 13.0
Solids: 18.4%

CONTACT INFORMATION

OFFICE:
1-888-6PURITY (678-7489)
FAX
1-877-9PURITY (978-7489)
ADDRESS:
114 SOUTHFIELD PKWY
SUITE 120
FOREST PARK GA. 30297
www.puritychemicals.com



HMIS RATINGS:
Health: 3
Flammability: 0
Reactivity: 0
Personal Protection: D

Section 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Trade Name: ALKA 200
Chemical Family: Alkali Cleaner
Company Identification: ABC COMPOUNDING CO., INC.
P.O. BOX 16247
ATLANTA, GA

Emergency Telephone Number: (800)535-5053
Date Prepared: AUG 20, 2003
MSDS Number: LA-506
MFGD. BY: ABC Compounding Co., Inc.
6970 Jonesboro Rd.
Morrow, Ga. 30260

Section 2: COMPOSITION, INFORMATION ON INGREDIENTS

CAS NUMBER	CHEMICAL NAME	% BY WGT.	OSHA PEL/ACGIH TLV	SARA 302/304 (1) *	SARA 313 (2) *	STATE INFO (3) (4) RQ	CERCLA
64-02-8	Tetrasodium Ethylenediamine-tetraacetic acid Sodium Silicate	< 8.0	n/e / n/e	NO	NO	NO	
1344-09-8		< 7.0	2 mg/m3 / 2 mg/m3	NO	NO	NO	
34590-94-8	Dipropylene Glycol Monomethyl Ether	< 2.0	n/e / n/e	NO	NO	NO	
1310-58-3	Potassium Hydroxide	< 2.0	2 mg/m3 / 2 mg/m3	NO	NO	NO	1000 Lbs

* See Section 15 for more information n/e = none established - n/a = not applicable

Section 3: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER. Corrosive. May cause moderate to severe eye and skin irritation. May be harmful or fatal if swallowed.

Primary Route of Entry: Eye contact, skin contact

Acute/Potential Health Effects:

EYES: Causes severe irritation experienced as discomfort or pain, excess blinking and tear production, with redness and swelling of the conjunctiva.

SKIN: Brief contact may cause slight irritation. Prolonged contact may cause more severe irritation with pain, local redness and swelling and possible tissue destruction.

INHALATION: High concentrations of vapor or mists may cause irritation of the respiratory tract.

INGESTION: Harmful or fatal if swallowed. Corrosive. Can cause severe burns and complete tissue perforation of mucous membranes, mouth, throat and stomach.

Skin Protection: Wear impervious gloves (made from rubber, nitrile or neoprene) clothing and boots.

Respiratory Protection: When respiratory protection is required, use an organic vapor & particulate cartridge. All respiratory programs must meet OSHA's 29 CFR 1910.34 & ANSI Z88.2 requirements.

Engineering Controls: Good general ventilation required.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance and Odor: Clear, colorless odorless liquid
pH Concentrate: 13.0
Solubility in Water: Complete
Vapor Pressure [mmHg]: n/e
Evaporation Rate [Butyl Acetate=1]: n/e
Vapor Density [Air=1]: n/e
Specific Gravity [H2O=1]: 1.11
Boiling Point: > 212 F

Section 10: REACTIVITY

Stability: Stable
Hazardous Polymerization: Will not occur
Conditions to avoid: High temperature
Hazardous Decomposition Products: None
Incompatibility: Strong acids, water, certain metals (aluminum)

Section 11: TOXICOLOGICAL INFORMATION

No data.

Section 12: ECOLOGICAL INFORMATION

No data.

Section 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method:

Waste must be disposed of in accordance with federal, state and local environmental control regulations.

Section 14: TRANSPORTATION INFORMATION

D.O.T. Shipping Name / Class:

Corrosive Liquid, Basic, Inorganic, N.O.S., 8, UN 3266, II

(Contains Potassium Hydroxide)

Section 15: REGULATORY INFORMATION

U.S. Federal Regulations:

TSCA (Toxic Substances Control Act): The intentional ingredients of product are listed.

Section 3: HAZARDS IDENTIFICATION - continued:

Chronic / Long Term Effects: No data.

Signs and Symptoms of Overexposure: Dermal exposure may cause local redness and swelling, pain and discomfort.

Target Organ Effects: Lungs and upper respiratory tract, gastrointestinal tract, eyes, skin.

Reproductive/Developmental Information: No data.

Carcinogenic Information: This material is not listed as a carcinogen by IARC, NTP or OSHA.

Section 4: FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.

SKIN: Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Get medical attention immediately.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

INGESTION: Seek medical attention immediately. Do not induce vomiting. If victim is alert, give 1/2 to 1 glass of water. Call a poison control center or doctor for treatment advice.

Section 5: FIRE FIGHTING MEASURES

Flash Point: No flash by standard methods

Extinguishing Media: Dry chemical, CO2 or foam is recommended.

Special Fire Fighting Instructions: Wear a self contained breathing apparatus with a full face piece operated in the positive pressure demand mode. Chemical resistant PPE is recommended.

Section 6: ACCIDENTAL RELEASE MEASURES

Stop all leaks. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Absorb spill with inert material (e.g. dry sand, earth). Prevent runoff from entering drains, sewers or other bodies of water. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal.

Section 7: HANDLING AND STORAGE

Follow all MSDS/label precautions even after container is emptied because they may contain product residues. Use with adequate ventilation. Do not get in eyes, on skin or clothing. Store in a cool, dry place. Keep container closed when not in use. Keep out of reach of children.

Section 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Eye Protection: Wear safety glasses or goggles and face shield. Remove contact lenses.

Title III Section 311/312 Hazardous Categories - 40 CFR 370.2:
ACUTE (X) Chronic (X) Fire () Pressure () Reactive () Not Applicable ()

(1) Title III Section 302/304 Extremely Hazardous Substances - 40 CFR 355 Appendix A

(2) Title III Section 313 Toxic Chemicals - 40 CFR 372.65

If indicated under Section 2 of this MSDS, this product contains toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning & Community Right to Know Act of 1986. This information must be included in all MSDS that are copied and distributed for this material.

RCRA Status: Under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste. If this product becomes a hazardous waste it would be assigned RCRA Code(s) D002

State and Local Regulations: Certain states maintain their own ingredient lists which differ slightly from the Federal standards. If indicated under Section 2 of this MSDS, states listed below may have regulations on ingredients contained in this product. Check with your state for any additional regulations.

(3) California proposition 65 (Safe Drinking Water & Toxic Enforcement Act of 1986)
(4) Massachusetts (Hazardous Substance Disclosure by Employers)

Section 16: OTHER INFORMATION

This information was compiled from current manufacturer's MSDS's of the component parts of the product.

Disclaimer: The Manufacturer believes that the information contained in the Material Safety Data Sheet is accurate. The suggested procedures are based on experience as of the date of publication. They are not necessarily all inclusive nor fully adequate in every circumstance. Also, the suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements.